INSAUSTI®

DIFFICULT INTUBATION - SIMPLE TROLLEY 300 SERIES
3708 W

DIMENSIONS 640 x 480 mm
ADEQUATE HEIGHT, ERGONOMICS 980 mm (work surface – floor).

WORK SURFACE
- Polyethylene, PE. Asepsis, hygiene, easy-to-clean.
- Withstands alcohol, detergents, disinfectants, chlorhexidine.
- Protection on all 4 sides. Pleasant to the touch, rounded shapes.
- Raised sides make it possible to move the trolley without needing the push handle.

MONOBLOC STRUCTURE
- Stainless steel AISI-304. Fine satin finish, asepsis, hygiene.

ISO DRAWER FRAMEWORK
- Total opening.
- Steel ball-bearing slides with self-closing system.
- Front stop, it protects the slide against strong impacts when closing.
- Load capacity per drawer: 20 kg.
- Interior frame ISO 600 x 400 mm.
- Polyethylene drawer front part, thickness 10 mm, 6 colours (Ref. G, Y, W, B, F, R).
- Ergonomic handle.
- Card holder with white cards, removable.

ISO DRAWERS 600 x 400 mm
- Heights 50, 100, 200 mm. Interchangeable, ABS.
- ISO norm 3394.

STATIC TROLLEYS
- Without push handle - Easy left panel cleaning.
  - Free left side for mounting accessories.
- Double wheels Ø 100 mm. Soft tread, silent.
- 2 antistatic (electrical conductive), 2 with brake at the front part.

3708 W
364M6 W.12B.14.26LW(R2).32R.36.44L

ACCESSORIES

12B INDIVIDUAL MANUAL LOCKING

14 NUMBERED DISPOSABLE SEALS

26LW(R2) CENTRAL SHELF

32R SIDE SUPPORT

36 GAS BOTTLE STAND

44L CATHETERS CONTAINER